

BẢNG GIÁ BIẾN TẦN LS - HÀN QUỐC



(Áp dụng từ ngày **15-05-2024**)

Tên hàng	KW	HP	In (A)		Mô tả	Đơn giá (VNĐ)	
3Ø 200V Class 0.4~7.5KW * Non-Filter Type.			HD	ND			
LSLV0004G100-2EONN	0.4KW	0.5HP	2.5A	3.1A	Biến tần đa năng: Sử dụng trong tất cả các ngành công nghiệp bao gồm gia công kim loại, máy đúc, thiết bị thủy lực/ điều hòa không khí, thực phẩm và đồ uống/ máy dệt, thang máy/ băng tải và xử lý môi trường nước. . Máy cắt/ uốn/ đánh bóng . Quạt/ Bơm . Máy ép/ băng tải . Máy hút bụi/ tu động . Máy nén/ thổi . Cầu trục (Nâng hạ, xe con, xe cầu)	4,050,000	
LSLV0008G100-2EONN	0.75KW	1HP	5A	6A		4,400,000	
LSLV0015G100-2EONN	1.5KW	2HP	8A	9.6A		5,050,000	
LSLV0022G100-2EONN	2.2KW	3HP	11A	12A		5,950,000	
LSLV0040G100-2EONN	4KW	5HP	17A	18A		6,700,000	
LSLV0055G100-2EONN	5.5KW	7.5HP	24A	30A		9,950,000	
LSLV0075G100-2EONN	7.5KW	10HP	32A	40A		11,150,000	
LSLV0110G100-2EONN	11KW	15HP	47A	56A		20,800,000	
LSLV0150G100-2EONN	15KW	20HP	60A	70A		23,900,000	
LSLV0185G100-2EONN	18.5KW	25HP	75A	82A		27,600,000	
LSLV0220G100-2EONN	22KW	30HP	88A		32,600,000		
3Ø 400V Class 0.4~7.5KW * Non-Filter Type.			HD	ND			
LSLV0004G100-4EONN	0.4KW	0.5HP	1.3A	2A	 <p>*HD (Heavy Duty): Tải nặng 150% dòng định mức/1 phút ** ND (Normal Duty): Tải nhẹ 120% dòng định mức/1 phút</p>	4,340,000	
LSLV0008G100-4EONN	0.75KW	1HP	2.5A	3.1A		4,600,000	
LSLV0015G100-4EONN	1.5KW	2HP	4A	5.1A		5,050,000	
LSLV0022G100-4EONN	2.2KW	3HP	5.5A	6.9A		5,700,000	
LSLV0040G100-4EONN	4KW	5HP	9A	10A		6,750,000	
LSLV0055G100-4EONN	5.5KW	7.5HP	12A	16A		9,550,000	
LSLV0075G100-4EONN	7.5KW	10HP	16A	23A		10,500,000	
LSLV0110G100-4EONN	11KW	15HP	47A	56A		18,300,000	
LSLV0150G100-4EONN	15KW	20HP	60A	70A		20,000,000	
LSLV0185G100-4EONN	18.5KW	25HP	75A	82A		23,700,000	
LSLV0220G100-4EONN	22KW	30HP	88A			25,800,000	
3Ø 400V Class 0.4~7.5KW * Built-in Filter (C3)			HD	ND			
LSLV0004G100-4EOFN	0.4KW	0.5HP	1.3A	2A		 <p>User-friendly Design</p> <p>G100 is convenient to install, control, G100 is convenient for installation, control, and maintenance with diverse functions.</p> <ul style="list-style-type: none"> Built-in Potentiometer Easy operation with built-in potentiometer Smart Copier Copy parameter (Read/Write) and download firmware without supplying power to drive Remote Keypad Copy parameter (Read/Write) using remote keypad 	4,600,000
LSLV0008G100-4EOFN	0.75KW	1HP	2.5A	3.1A	4,900,000		
LSLV0015G100-4EOFN	1.5KW	2HP	4A	5.1A	5,300,000		
LSLV0022G100-4EOFN	2.2KW	3HP	5.5A	6.9A	6,000,000		
LSLV0040G100-4EOFN	4KW	5HP	9A	10A	7,150,000		
LSLV0055G100-4EOFN	5.5KW	7.5HP	12A	16A	10,100,000		
LSLV0075G100-4EOFN	7.5KW	10HP	16A	23A	11,000,000		
LSLV0110G100-4EOFN	11KW	15HP	47A	56A	19,100,000		
LSLV0150G100-4EOFN	15KW	20HP	60A	70A	20,500,000		
LSLV0185G100-4EOFN	18.5KW	25HP	75A	82A	24,400,000		
LSLV0220G100-4EOFN	22KW	30HP	88A		26,500,000		
LOADER REMOTE 2M (LSLV-G100),A2MT-G100					Bàn phím dùng gắn ngoài kèm cáp kết nối loại 2 mét		1,000,000

THIẾT BỊ ĐIỆN

Tên hàng	KW	HP	In (A)		Mô tả	Đơn giá (VNĐ)
Loại 3 pha 380~480VAC			HD	ND	: V/f, V/f PG, sensorless vector, sensored vector, C/TVT dual ratings, built-in RS485(LS Bus / Modbus RTU)	
SV0008IS7-2NO	0.75	1HP	5A	8A	BIẾN TẦN HIỆU SUẤT CAO	10,200,000
SV0015IS7-2NO	1.5	2HP	8A	12A	IS7 là một biến tần với hiệu suất và độ tin cậy cao có thể áp dụng cho mọi môi trường làm việc. Mục đích sử dụng:	10,640,000
SV0022IS7-2NO	2.2	3HP	12A	16A		11,320,000
SV0037IS7-2NO	3.7	5HP	16A	24A	. Máy dầm, máy cán, máy kéo	11,650,000
SV0055IS7-2NO	5.5	7.5HP	24A	32A	. Dây chuyền lắp ráp lốp xe	13,200,000
SV0075IS7-2NO	7.5	10HP	32A	46A	. Thang máy, cần trục, cầu trục	14,500,000
SV0110IS7-2NO	11	15HP	46A	60A	. Thiết bị đỗ xe, kho hàng tự động	22,900,000
SV0150IS7-2NO	15	20HP	60A	74A	. Máy ép, máy rửa, máy khử nước, máy nén...	25,600,000
SV0185IS7-2NO	18.5	25HP	74A	88A	3 phase, 200~230VAC(+10%,-15%), 50~60Hz(±5%), 0.01~400Hz,, tích hợp transistor điều khiển điện trở thẳng	34,400,000
SV0220IS7-2NO	22	30HP	88A	124A		39,000,000
SV0300IS7-2SO	30	40HP	116A	146A	3 phase, 200~230VAC(+10%,-15%), 50~60Hz(±5%), 0.01~400Hz, built-in keypad	58,200,000
SV0370IS7-2SO	37	50HP	146A	180A		67,800,000
SV0450IS7-2SO	45	60HP	180A	220A		76,500,000
SV0550IS7-2SO	55	75HP	220A	288A		101,500,000
SV0750IS7-2SO	75	100HP	288A	345A		112,700,000
Loại 3 pha 380~480VAC			HD	ND	Built-in RS485(LS Bus / Modbus RTU)/ Ứng dụng cho các tải nặng như băng tải, máy khuấy, máy nén..., N: Chưa có màn hình, D: Tích hợp DC Reactor, Từ 0.75-	
SV0008IS7-4NO	0.75	1HP	2.5A	4A		9,900,000
SV0015IS7-4NO	1.5	2HP	4A	6A		10,300,000
SV0022IS7-4NO	2.2	3HP	6A	8A		10,900,000
SV0037IS7-4NO	3.7	5HP	8A	12A		11,100,000
SV0055IS7-4NO	5.5	7.5HP	12A	16A		12,700,000
SV0075IS7-4NO	7.5	10HP	16A	24A		13,800,000
SV0110IS7-4NO	11	15HP	24A	30A		21,300,000
SV0150IS7-4NO	15	20HP	30A	39A		23,600,000
SV0185IS7-4NO	18.5	25HP	39A	45A		29,200,000
SV0220IS7-4NO	22	30HP	45A	61A		3 pha, 380~480VAC(+10%,-15%),50~60Hz (±5%), 0.01~400Hz, tích hợp transistor điều khiển điện trở thẳng
SV0300IS7-4NO	30	40HP	62A	75A	3 pha, 380~480VAC(+10%,-15%), 50~60Hz(±5%), 0.01~400Hz	49,300,000
SV0370IS7-4NO	37	50HP	75A	91A		53,600,000
SV0450IS7-4NO	45	60HP	92A	110A		63,400,000
SV0550IS7-4NO	55	75HP	111A	152A		70,100,000
SV0750IS7-4NO	75	100HP	152A	183A		83,300,000


THIẾT BỊ ĐIỆN

	KW	HP	In (A)		Mô tả	Đơn giá (VNĐ)
SV0008IS7-4NOFD	0.75	1HP	2.5A	4A	3 pha, 380~480VAC(+10%,-15%), 50~60Hz(±5%), 0.01~400Hz, tích hợp transistor điều khiển điện trở thẳng, bộ lọc EMC, cuộn kháng DC	12,200,000
SV0015IS7-4NOFD	1.5	2HP	4A	6A		12,900,000
SV0022IS7-4NOFD	2.2	3HP	6A	8A		13,500,000
SV0037IS7-4NOFD	3.7	5HP	8A	12A		13,900,000
SV0055IS7-4NOFD	5.5	7.5HP	12A	16A		16,000,000
SV0075IS7-4NOFD	7.5	10HP	16A	24A		17,300,000
SV0110IS7-4NOFD	11	15HP	24A	30A		26,800,000
SV0150IS7-4NOFD	15	20HP	30A	39A		31,200,000
SV0185IS7-4NOFD	18.5	25HP	39A	45A		37,800,000
SV0220IS7-4NOFD	22	30HP	45A	61A		42,700,000
SV0300IS7-4NOD	30	40HP	65A	75A	3 pha, 380~480VAC(+10%,-15%), 50~60Hz(±5%), 0.01~400Hz, tích hợp cuộn kháng DC	54,800,000
SV0370IS7-4NOD	37	50HP	75A	91A		61,000,000
SV0450IS7-4NOD	45	60HP	91A	110A		72,100,000
SV0550IS7-4NOD	55	75HP	110A	152A		80,700,000
SV0750IS7-4NOD	75	100HP	152A	183A		91,500,000
SV0900IS7-4SOD	90	125HP	183A	223A	3 pha, 380~480VAC(+10%,-15%), 50~60Hz(±5%), 0.01~400Hz, tích hợp cuộn kháng DC, bàn phím	139,800,000
SV1100IS7-4SOD	110	150HP	223A	264A		148,500,000
SV1320IS7-4SOD	132	175HP	264A	325A		164,500,000
SV1600IS7-4SOD	160	215HP	325A	370A		211,900,000
SV1850IS7-4SOD	185	250HP	370A	432A		287,200,000
SV2200IS7-4SOD	220	300HP	432A	547A		302,300,000
SV2800IS7-4SO	285	350HP	547A	613A	3 pha, 380~480VAC(+10%,-15%), 50~60Hz(±5%), 0.01~400Hz, bàn phím	523,200,000
SV3150IS7-4SO	315	400HP	613A	731A		641,500,000
SV3750IS7-4SO	375	500HP	731A	877A		689,700,000
SV-IS7 LCD Key pad					Bảng điều khiển màn hình màu dùng cho iS7 (đa ngôn ngữ: English, Italian, Spanish, Russian, Turkish)	1,420,000
Remote cable 2m (for IS7)					Cáp kết nối bảng điều khiển và biến tần iS7 loại 2 mét	390,000
Remote cable 3m (for IS7)					Cáp kết nối bảng điều khiển và biến tần iS7 loại 3 mét	420,000
OPTION PROFIBUS-DP,SV-IS7						4,100,000
OPTION EXTENSION I/O,SV-IS7						3,080,000
ENCODER OPTION ,SV-IS7						1,450,000

BẢNG GIÁ BIẾN TẦN LS - HÀN QUỐC




(Áp dụng từ ngày **15-05-2024**)

Biến tần cho quạt và bơm: Loại 3 Pha 220~230VAC - IP20				ND	V/f, RS485(LS Bus / Modbus RTU / BACnet / Metasys N2), Pulse train I/O, RTC(Real Time Clock), đã có màn hình (HAND/OFF/AUTO), USB Port/ Ứng dụng chuyên cho hệ HVAC, Bơm, Quạt...
LSLV0055H100-2CONN	5.5kW	7.5HP		22A	BIẾN TẦN CHO QUẠT VÀ BƠM Dùng trong các ngành công nghiệp: xây dựng, kim loại, bột giấy/ giấy, mỏ than, xử lý dầu khí và nước; (quạt/ bơm, máy sấy)
LSLV0075H100-2CONN	7.5kW	10HP		30A	
LSLV0110H100-2CONN	11KW	15HP		42A	
LSLV0150H100-2CONN	15KW	20HP		59A	
LSLV0185H100-2CONN	18.5KW	25HP		69A	
Biến tần cho quạt và bơm: Loại 3 Phase 380~480VAC - IP20, IP00				ND	
LSLV0055H100-4COFN	5.5kW	7.5HP		12A	 Built-in Dynamic braking transistor, EMC Filter(C3)
LSLV0075H100-4COFN	7.5kW	10HP		16A	
LSLV0110H100-4COFN	11KW	15HP		24A	
LSLV0150H100-4COFN	15KW	20HP		30A	
LSLV0185H100-4COFN	18.5KW	25HP		38A	
LSLV0220H100-4COFN	22KW	30HP		45A	
LSLV0300H100-4COFN	30KW	40HP		61A	
LSLV0370H100-4COND	37KW	50HP		75A	
LSLV0450H100-4COND	45KW	60HP		91A	
LSLV0550H100-4COND	55KW	75HP		107A	
LSLV0370H100-4COFD	37KW	50HP		75A	3 phase, 380~480VAC(+10%,-15%), 50~60Hz(±5%), 0.1~400Hz, IP20, built-in DC Reactor
LSLV0450H100-4COFD	45KW	60HP		91A	
LSLV0550H100-4COFD	55KW	75HP		107A	
LSLV0750H100-4COFD	75KW	100HP		142A	3 phase, 380~480VAC(+10%,-15%), 50~60Hz(±5%), 0.1~400Hz, built-in EMC Filter(C3), DC Reactor
LSLV0900H100-4COFD	90KW	125HP		169A	
LSLV1100H100-4COFD	110KW	150HP		223	
LSLV1320H100-4COFD	132KW	200HP		264	3 phase, 380~500VAC(+10%,-15%), 50~60Hz(±5%), 0.1~400Hz, IP20, built-in EMC Filter(C3), DC Reactor
LSLV1600H100-4COFD	160KW	250HP		325	
LSLV1850H100-4COFD	185KW	300HP		370	
LSLV2200H100-4COFD	220KW	350HP		432	220kW(350HP), 3 phase, 380~500VAC(+10%,-15%), 50~60Hz(±5%), 0.1~400Hz, IP00, built-in EMC Filter(C3), DC Reactor
LSLV2500H100-4COFD	250KW	400HP		481	
LSLV3150H100-4COFD	315KW	500HP		613	
LSLV3550H100-4COFD	355KW	550HP		683	
LSLV4000H100-4COFD	400KW	650HP		770	
LSLV5000H100-4COFD	500KW	800HP		962	
- GHI CHÚ:		**HD(Heavy Duty) Overload 150% 1min.			
		**ND(Normal Duty): Overload 110% or 120% 1min			

BẢNG GIÁ BIẾN TẦN LS - HÀN QUỐC



(Áp dụng từ ngày **15-05-2024**)

Tên hàng	KW	HP	Overload capacity	Output (A)	Mô tả	Đơn giá (VNĐ)
Loại 1 pha 200~240VAC - IP20						
			HD	ND	: V/f, fixed keypad, EMC filter(C2)	
LSLV0001M100-1EOFNS	0.1KW	1/8HP	0.8A	-	BIẾN TẦN MICRO: - Sử dụng cho các máy móc, quạt/ bơm và băng tải nhỏ. - Lắp đặt trên thanh Din Rail.  EOFNS: (Standard I/O: 3 Digital Inputs, 1 Analog Input, 1 Analog Output, 1 Open Collector, 1 Relay) EOFNA: (Advanced I/O: 5 Digital Inputs, 2 Analog Input, 1 Analog Output, 1 Open Collector, 2 Relay, RS485)	2,850,000
LSLV0002M100-1EOFNS	0.2KW	1/4HP	1.4A	-		2,950,000
LSLV0004M100-1EOFNS	0.4KW	1/2HP	2.4A	-		3,150,000
LSLV0008M100-1EOFNS	0.75KW	1HP	4.2A	-		3,300,000
LSLV0015M100-1EOFNS	1.5KW	2HP	7.5A	-		3,950,000
LSLV0022M100-1EOFNS	2.2KW	3HP	10A	-		4,350,000
LSLV0001M100-1EOFNA	0.1KW	1/8HP	0.8A	-		3,100,000
LSLV0002M100-1EOFNA	0.2KW	1/4HP	1.4A	-		3,200,000
LSLV0004M100-1EOFNA	0.4KW	1/2HP	2.4A	-		3,400,000
LSLV0008M100-1EOFNA	0.75KW	1HP	4.2A	-		3,600,000
LSLV0015M100-1EOFNA	1.5KW	2HP	7.5A	-		4,300,000
LSLV0022M100-1EOFNA	2.2KW	3HP	10A	-		4,650,000

Tên hàng	KW	HP	Overload capacity	Output (A)	Mô tả	Đơn giá (VNĐ)	
L100 series for Elevator Application:							
Biến tần thang máy							
LSLV0055L100-4NNFN	5.5	7.5	50% for 1 min	12	- Khả dụng cho nhiều loại tải khác nhau (Thang khách, thang hàng, thang máy đồ xe,...) - Có thể điều khiển động cơ IM hoặc động cơ PM, có hộp số hay không có hộp số - Điều khiển vector vòng hở và vector vòng kín cho động cơ IM hoặc PM tiêu chuẩn (với Incremental encoder, SIN/COS encoder, Endat encoder) - Kích thước nhỏ gọn cho phép lắp đặt không phòng máy.	Call	
LSLV0075L100-4NNFN	7.5	10	50% for 1 min	16		Call	
LSLV0110L100-4NNFN	11	15	50% for 1 min	24		Call	
LSLV0150L100-4NNFN	15	20	50% for 1 min	30		Call	
LSLV0185L100-4NNFN	18.5	25	50% for 1 min	39		Call	
LSLV0220L100-4NNFN	22	30	50% for 1 min	45		Call	
ENCODER(LSLV-L100),XENC-L100							Call
SIN/COS ENCODER(LSLV-L100),XSIN-L100							Call
SIN/COS_ENDAT ENCODER(LSLV-L100),XEDT-100							Call
ELEVATOR I/O(LSLV-L100),XELV-L100							Call
REMOTE 2M(LSLV-L100),A2MT-L100						Call	
REMOTE 3M(LSLV-L100),A3MT-L100						Call	
REMOTE 5M(LSLV-L100),A5MT-L100						Call	
RS 232 CABLE 2M(LSLV-L100),S2MT-L100						Call	



BẢNG GIÁ BIẾN TẦN LS - HÀN QUỐC



(Áp dụng từ ngày **15-05-2024**)

Tên hàng	KW	HP	In (A)	Mô tả	Đơn giá (VNĐ)
Loại 1 pha 200~240VAC (Protection degree IP20)			HD	ND	Semi-Dual rating, V/f, sensorless vector control, RS485 (LS Bus / Modbus RTU), Safety Torque off, Pulse train I/O / Các ứng dụng cơ bản (bơm, quạt, băng tải, máy nén, máy cán...)
LSLV0004S 100-1EONNS	0.4/0.75kw	1/2HP	2.5A	-	Call
LSLV0008S 100-1EONNS	0.75/1.5kw	1HP	5A	-	1 phase, 200~240VAC(+10%,-15%), 50~60Hz(±5%), 0.1~400Hz, tích hợp bàn phím, điện trở thắt, control terminal I/O 5mm pitch
LSLV0015S 100-1EONNS	1.5/2.2kw	2HP	8A	-	
LSLV0022S 100-1EONNS	2.2/3.7kw	3HP	11A	-	
Loại 3 Pha 200~240VAC (Protection degree IP20)			HD	ND	
LSLV0004S 100-2EONNS	0.4/0.75kw	1/2HP	2.5A	-	Call
LSLV0008S 100-2EONNS	0.75/1.5kw	1HP	5A	-	Call
LSLV0015S 100-2EONNS	1.5/2.2kw	2HP	8A	-	Call
LSLV0022S 100-2EONNS	2.2/3.7kw	3HP	11A	-	Call
LSLV0037S 100-2EONNS	3.7/4kw	5HP	16A	-	Call
LSLV0040S 100-2EONNS	4/5.5kw	5.4HP	17A	-	Call
LSLV0055S 100-2EONNS	5.5/7.5kw	7.5HP	24A	-	Call
LSLV0075S 100-2EONNS	7.5/11kw	10HP	32A	-	Call
LSLV0110S 100-2EONNS	11/15kw	15HP	46A	-	3 phase, 200~240VAC(+10%,-15%), 50~60Hz(±5%), 0.1~400Hz, tích hợp bàn phím, điện trở thắt, control terminal I/O 5mm pitch
LSLV0150S 100-2EONNS	15/18.5kw	20HP	60A	-	
Loại 3 Pha 380~480VAC (Protection degree IP20)			HD	ND	Semi-Dual rating, V/f, sensorless vector control, RS485 (LS Bus / Modbus RTU), Safety Torque off, Pulse train I/O / Các ứng dụng cơ bản (bơm, quạt, băng tải...)
LSLV0004S 100-4EONNS	0.4/0.75kw	1/2HP	1.25A	-	3 phase, 380~480VAC(+10%,-15%), 50~60Hz(±5%), 0.1~400Hz, tích hợp bàn phím, điện trở thắt, control terminal I/O 5mm pitch
LSLV0008S 100-4EONNS	0.75/1.5kw	1HP	2.5A	-	
LSLV0015S 100-4EONNS	1.5/2.2kw	2HP	4A	-	
LSLV0022S 100-4EONNS	2.2/3.7kw	3HP	5.5A	-	
LSLV0037S 100-4EONNS	3.7/4kw	5HP	8A	-	
LSLV0040S 100-4EONNS	4/5.5kw	5.4HP	9A	-	
LSLV0055S 100-4EONNS	5.5/7.5kw	7.5HP	12A	-	3 phase, 380~480VAC(+10%,-15%), 50~60Hz(±5%), 0.1~400Hz, tích hợp bàn phím, điện trở thắt, EMC filter(C3), control terminal I/O 5mm pitch
LSLV0075S 100-4EONNS	7.5/11kw	10HP	16A	-	
LSLV0110S 100-4EONNS	11/15kw	15HP	24A	-	
LSLV0150S 100-4EONNS	15/18.5kw	20HP	30A	-	
LSLV0185S 100-4EONNS	18.5/22kw	25HP	39A	-	
LSLV0220S 100-4EONNS	22/30kw	30HP	45A	-	
LSLV0300S 100-4CONDS	30/37kw	40HP	61A	-	3 phase, 380~480VAC(+10%,-15%), 50~60Hz(±5%), 0.1~400Hz, detachable LCD keypad, built-in DC reactor, control terminal I/O 5mm pitch
LSLV0370S 100-4CONDS	37/45kw	50HP	75A	-	
LSLV0450S 100-4CONDS	45/55kw	60HP	91A	-	
LSLV0550S 100-4CONDS	55/75kw	75HP	110A	-	
LSLV0750S 100-4CONDS	75/90kw	100HP	152A	-	



Loại 3 Pha 200~230VAC (Protection degree IP66 (NEMA4X))			HD	ND	Semi-Dual rating, V/f, sensorless vector control, RS485 (LS Bus / Modbus RTU), Safety Torque off, Pulse train I/O/ Các ứng dụng cơ bản (bơm, quạt, băng tải...)	
LSLV0004S100-2EXNNS	0.4/0.75kw	1/2HP	2.5A	-	3 phase, 200~240VAC(+10%,-15%), 50~60Hz(±5%), 0.1~400Hz, tích hợp bàn phím, điện trở thẳng, control terminal I/O 5mm pitch	Call
LSLV0008S100-2EXNNS	0.75/1.5kw	1HP	5A	-		Call
LSLV0015S100-2EXNNS	1.5/2.2kw	2HP	8A	-		Call
LSLV0022S100-2EXNNS	2.2/3.7kw	3HP	11A	-		Call
LSLV0037S100-2EXNNS	3.7/4kw	5HP	16A	-		Call
LSLV0040S100-2EXNNS	4/5.5kw	5.4HP	17A	-		Call
LSLV0055S100-2EXNNS	5.5/7.5kw	7.5HP	24A	-		Call
LSLV0075S100-2EXNNS	7.5/11kw	10HP	32A	-		Call
LSLV0110S100-2EXNNS	11/15kw	15HP	46A	-		Call
LSLV0150S100-2EXNNS	15/18.5kw	20HP	60A	-		Call
Loại 3 Phase 380~480VAC (Protection degree IP66 (NEMA4X))			HD	ND	Semi-Dual rating, V/f, sensorless vector control, RS485 (LS Bus / Modbus RTU), Safety Torque off, Pulse train I/O/ Các ứng dụng cơ bản (bơm, quạt, băng tải...)	
LSLV0004S100-4EXNNS	0.4/0.75kw	1/2HP	1.25A	-	3 phase, 380~480VAC(+10%,-15%), 50~60Hz(±5%), 0.1~400Hz, tích hợp bàn phím, điện trở thẳng, control terminal I/O 5mm pitch	Call
LSLV0008S100-4EXNNS	0.75/1.5kw	1HP	2.5A	-		Call
LSLV0015S100-4EXNNS	1.5/2.2kw	2HP	4A	-		Call
LSLV0022S100-4EXNNS	2.2/3.7kw	3HP	5.5A	-		Call
LSLV0037S100-4EXNNS	3.7/4kw	5HP	8A	-		Call
LSLV0040S100-4EXNNS	4/5.5kw	5.4HP	9A	-		Call
LSLV0055S100-4EXNNS	5.5/7.5kw	7.5HP	12A	-		Call
LSLV0075S100-4EXNNS	7.5/11kw	10HP	16A	-		Call
LSLV0110S100-4EXNNS	11/15kw	15HP	24A	-		Call
LSLV0150S100-4EXNNS	15/18.5kw	20HP	30A	-		Call
LSLV0185S100-4EXNNS	18.5/22kw	25HP	39A	-		Call
LSLV0220S100-4EXNNS	22/30kw	30HP	45A	-		Call
Phụ kiện dùng cho LSLV S100:						
CANOpen(LSLV-S100),CCAN-S100						Call
Profibus-DP(LSLV-S100),CPDP-S100						Call
Ethernet(LSLV-S100),CENT-S100						Call
- GHI CHÚ:		**HD(Heavy Duty) Overload 150% 1min.				
		**ND(Normal Duty): Overload 110% or 120% 1min				

BẢNG GIÁ BIẾN TẦN LS - HÀN QUỐC



(Áp dụng từ ngày **15-05-2024**)

Tên hàng		Mô tả	Đơn giá (VNĐ)
Dynamic Braking Unit (DBU) Bộ Transistor để gắn Điện trở xả vào.			
Dynamic Braking Unit (DBU) - 200~230V			
LSLV0150DBU-2LN	Brake unit for 15kW, 220V / 150% Average Braking Torque / 5~10%ED (Enable Duty)	4,200,000	
LSLV0220DBU-2LN	Brake unit for 22kW, 220V / 150% Average Braking Torque / 5~10%ED (Enable Duty)	4,850,000	
LSLV0370DBU-2LN	Brake unit for 37kW, 220V / 150% Average Braking Torque / 5~10%ED (Enable Duty)	5,850,000	
LSLV0370DBU-2HN	Brake unit for 37kW, 220V / 150% Average Braking Torque / 5~50%ED (Enable Duty)	13,392,000	
LSLV0750DBU-2LN	Brake unit for 75kW, 220V / 150% Average Braking Torque / 5~10%ED (Enable Duty)	8,100,000	
LSLV0750DBU-2HN	Brake unit for 75kW, 220V / 150% Average Braking Torque / 5~50%ED (Enable Duty)	20,000,000	
LSLV0900DBU-2HN	Brake unit for 90kW, 220V / 150% Average Braking Torque / 5~50%ED (Enable Duty)	22,150,000	
Dynamic Braking Unit (DBU) - 380~400V			
LSLV0150DBU-4LN	Brake unit for 15kW, 440V / 150% Average Braking Torque / 5~10%ED (Enable Duty)	4,200,000	
LSLV0220DBU-4LN	Brake unit for 22kW, 440V / 150% Average Braking Torque / 5~10%ED (Enable Duty)	4,850,000	
LSLV0370DBU-4LN	Brake unit for 37kW, 440V / 150% Average Braking Torque / 5~10%ED (Enable Duty)	5,850,000	
LSLV0370DBU-4HN	Brake unit for 37kW, 440V / 150% Average Braking Torque / 5~50%ED (Enable Duty)	12,750,000	
LSLV0750DBU-4LN	Brake unit for 75kW, 440V / 150% Average Braking Torque / 5~10%ED (Enable Duty)	7,450,000	
LSLV0750DBU-4HN	Brake unit for 75kW, 440V / 150% Average Braking Torque / 5~50%ED (Enable Duty)	18,150,000	
INV,SV750DB-4	Brake unit for 75kW, 440V / 150% Average Braking Torque / 100%ED (Enable Duty), CE certificated	25,400,000	
LSLV0900DBU-4HN	Brake unit for 90kW, 440V / 150% Average Braking Torque / 5~50%ED (Enable Duty)	22,150,000	
LSLV1320DBU-4HN	Brake unit for 132kW, 440V / 150% Average Braking Torque / 5~50%ED (Enable Duty)	27,000,000	
LSLV1600DBU-4HN	Brake unit for 160kW, 440V / 150% Average Braking Torque / 5~50%ED (Enable Duty)	36,700,000	
LSLV2200DBU-4HN	Brake unit for 220kW, 440V / 150% Average Braking Torque / 5~50%ED (Enable Duty)	40,500,000	
INV,SV2200DB-4	Brake unit for 220kW, 440V / 150% Average Braking Torque / 100%ED (Enable Duty), CE certificated	31,300,000	

External brake resistors (Điện trở xả)		Temperature range: -50~200°C , Insulation resistance: over 100MΩ, Dielectric strength: AC 2,500V / 1 Min, Temperature coefficient: ±260 ppm / °C max	
Tên hàng		Mô tả	Đơn giá (VNĐ)
	MCRA 50W 1.8K OHM J	50 wat, 1800ohm resistor (Based on 5% ED (Enable duty))	280,000
	MCRA 100W 1.2K OHM J	100 wat, 1200ohm resistor (Based on 5% ED (Enable duty))	280,000
	MCRA 200W 1.2K OHM J	200 wat, 1200ohm resistor (Based on 5% ED (Enable duty))	430,000
	MCRA 100W 900 OHM J	100 wat, 900ohm resistor (Based on 5% ED (Enable duty))	200,000
	MCRA 150W 600 OHM J	150 wat, 600ohm resistor (Based on 5% ED (Enable duty))	240,000
	MCRA 200W 450 OHM J	200 wat, 450ohm resistor (Based on 5% ED (Enable duty))	330,000
	MCRA 50W 400 OHM J	50 wat, 400ohm resistor (Based on 5% ED (Enable duty))	190,000
	MCRA 100W 300 OHM J	100 wat, 300ohm resistor (Based on 5% ED (Enable duty))	200,000
	MCRA 200W 300 OHM J	200 wat, 300ohm resistor (Based on 5% ED (Enable duty))	330,000
	MCRA 100W 200 OHM J	100 wat, 200ohm resistor (Based on 5% ED (Enable duty))	200,000
	MCRA 150W 150 OHM J	150 wat, 150ohm resistor (Based on 5% ED (Enable duty))	240,000
	MCRA 200W 100 OHM J	200 wat, 100ohm resistor (Based on 5% ED (Enable duty))	330,000
	MCRF 300W 600 OHM J	300 wat, 600ohm resistor (Based on 5% ED (Enable duty))	520,000
	MCRF 300W 300 OHM J	300 wat, 300ohm resistor (Based on 5% ED (Enable duty))	460,000
	MCRF 600W 300 OHM J	600 wat, 300ohm resistor (Based on 5% ED (Enable duty))	680,000
	MCRF 400W 200 OHM J	400 wat, 200ohm resistor (Based on 5% ED (Enable duty))	570,000
	MCRF 800W 200 OHM J	800 wat, 200ohm resistor (Based on 5% ED (Enable duty))	760,000
	MCRF 300W 150 OHM J	300 wat, 150ohm resistor (Based on 5% ED (Enable duty))	470,000
	MCRF 600W 130 OHM J	600 wat, 130ohm resistor (Based on 5% ED (Enable duty))	680,000
	MCRF 1.2kW 130 OHM J	1200 wat, 130ohm resistor (Based on 5% ED (Enable duty))	940,000
	MCRF 700W 120 OHM J	700 wat, 120ohm resistor (Based on 5% ED (Enable duty))	750,000
	MCRF 1kW 90 OHM J	1000 wat, 90ohm resistor (Based on 5% ED (Enable duty))	810,000
	MCRF 1kW 85 OHM J	1000 wat, 85ohm resistor (Based on 5% ED (Enable duty))	810,000
	MCRF 2kW 85 OHM J	2000 wat, 85ohm resistor (Based on 5% ED (Enable duty))	1,550,000
	MCRF 300W 60 OHM J	300 wat, 60ohm resistor (Based on 5% ED (Enable duty))	470,000
	MCRF 600W 60 OHM J	600 wat, 60ohm resistor (Based on 5% ED (Enable duty))	680,000
	MCRF 1.2kW 60 OHM J	1200 wat, 60ohm resistor (Based on 5% ED (Enable duty))	940,000
	MCRF 400W 50 OHM J	400 wat, 50ohm resistor (Based on 5% ED (Enable duty))	570,000
	MCRF 800W 50 OHM J	800 wat, 50ohm resistor (Based on 5% ED (Enable duty))	760,000
	MCRF 2kW 45 OHM J	2000 wat, 45ohm resistor (Based on 5% ED (Enable duty))	1,550,000
	MCRF 500W 40 OHM J	500 wat, 40ohm resistor (Based on 5% ED (Enable duty))	610,000
	MCRF 2kW 40 OHM J	2000 wat, 40ohm resistor (Based on 5% ED (Enable duty))	1,550,000
	MCRF 1.6kW 33.9 OHM J	1600 wat, 33.9ohm resistor (Based on 5% ED (Enable duty))	1,190,000
	MCRF 600W 33 OHM J	600 wat, 33ohm resistor (Based on 5% ED (Enable duty))	680,000
	MCRF 1.2kW 33 OHM J	1200 wat, 33ohm resistor (Based on 5% ED (Enable duty))	940,000
	MCRF 800W 20 OHM J	800 wat, 20ohm resistor (Based on 5% ED (Enable duty))	760,000
	MCRF 1.6kW 20 OHM J	1600 wat, 20ohm resistor (Based on 5% ED (Enable duty))	1,190,000
	MCRF 1.2kW 15 OHM J	1200 wat, 15ohm resistor (Based on 5% ED (Enable duty))	940,000
	MCRF 1.6kW 8.5 OHM J	1600 wat, 8.5ohm resistor (Based on 5% ED (Enable duty))	1,190,000
	MCRS 2.4kW 60 OHM J	2400 wat, 60ohm resistor (Based on 5% ED (Enable duty))	2,380,000
	MCRS 2.4kW 35 OHM J	2400 wat, 35ohm resistor (Based on 5% ED (Enable duty))	2,380,000
	MCRS 2.4kW 30 OHM J	2400 wat, 30ohm resistor (Based on 5% ED (Enable duty))	2,380,000
	MCRS 2.4kW 22.8 OHM J	2400 wat, 22.8ohm resistor (Based on 5% ED (Enable duty))	2,380,000
	MCRS 2.4kW 15 OHM J	2400 wat, 15ohm resistor (Based on 5% ED (Enable duty))	2,380,000
	MCRS 2.4kW 10 OHM J	2400 wat, 10ohm resistor (Based on 5% ED (Enable duty))	2,380,000
	MCRS 2.4kW 8 OHM J	2400 wat, 8ohm resistor (Based on 5% ED (Enable duty))	2,380,000
	MCRS 2.4kW 5.7 OHM J	2400 wat, 5.7ohm resistor (Based on 5% ED (Enable duty))	2,380,000

Brake resistors (Case package type with thermostat sensor)		Temperature range: -50~200°C , Insulation resistance: over 20MΩ, Dielectric strength: AC 2,500V / 1 Min, Temperature coefficient: ±260 ppm / °C max, Thermostat sensor: B contact	
Tên hàng		Mô tả	Đơn giá (VND)
	MCRF-ST 1.2kW 60 OHM J	1200 watt, 60 ohm resistor,	3,100,000
	MCRF-ST 2kW 45 OHM J	2000 watt, 45 ohm resistor	3,600,000
	MCRF-ST 2kW 40 OHM J	2000 watt, 40 ohm resistor	3,600,000
	MCRF-ST 4kW 40 OHM J	4000 watt, 40 ohm resistor	6,100,000
	MCRF-ST 2.4kW 35 OHM	2400 watt, 35 ohm resistor	4,300,000
	MCRF-ST 1.6kW 33.9 OHM J	1600 watt, 33.9 ohm resistor	3,600,000
	MCRF-ST 2.4kW 30 OHM J	2400 watt, 30 ohm resistor	4,300,000
	MCRF-ST 4.8kW 30 OHM J	4800 watt, 30 ohm resistor	7,300,000
	MCRF-ST 2.4kW 22.8 OHM J	2400 watt, 30 ohm resistor	4,300,000
	MCRF-ST 3.6kW 20 OHM J	3600 watt, 20 ohm resistor	5,400,000
	MCRF-ST 7.2kW 20 OHM J	7200 watt, 20 ohm resistor	8,900,000
	MCRF-ST 3.2kW 16.9 OHM J	3200 watt, 16.9 ohm resistor	5,400,000
	MCRF-ST 1.2kW 15 OHM J	1200 watt, 15 ohm resistor	3,100,000
	MCRF-ST 5kW 12 OHM J	5000 watt, 12 ohm resistor	7,300,000
	MCRF-ST 10kW 12 OHM J	10000 watt, 12 ohm resistor	12,500,000
	MCRF-ST 4.8kW 11.4 OHM J	4800 watt, 11.4 ohm resistor	7,300,000
	MCRF-ST 2.4kW 10 OHM J	2400 watt, 10 ohm resistor	4,300,000
	MCRF-ST 4.8kW 10 OHM J	4800 watt, 10 ohm resistor	7,300,000
	MCRF-ST 6.4kW 10 OHM J	6400 watt, 10 ohm resistor	8,800,000
	MCRF-ST 12.8kW 10 OHM J	12800 watt, 10 ohm resistor	15,900,000
	MCRF-ST 1.6kW 8.5 OHM J	1600 watt, 8.5 ohm resistor	3,600,000
	MCRF-ST 6.4kW 8.4 OHM J	6400 watt, 8.4 ohm resistor	8,800,000
	MCRF-ST 7.2kW 8.4 OHM J	7200 watt, 8.4 ohm resistor	8,900,000
	MCRF-ST 14.4kW 8.4 OHM J	14400 watt, 8.4 ohm resistor	16,500,000
	MCRF-ST 2.4kW 8 OHM J	2400 watt, 8 ohm resistor	4,300,000
	MCRF-ST 4.8kW 8 OHM J	4800 watt, 8 ohm resistor	7,300,000
	MCRF-ST 10kW 6 OHM J	10000 watt, 6 ohm resistor	12,500,000
	MCRF-ST 20kW 6 OHM J	20000 watt, 6 ohm resistor	23,200,000
	MCRF-ST 2.4kW 5.7 OHM J	2400 watt, 5.7 ohm resistor	4,300,000
	MCRF-ST 3.6kW 5 OHM J	3600 watt, 5 ohm resistor	5,400,000
	MCRF-ST 7.2kW 5 OHM J	7200 watt, 5 ohm resistor	8,900,000
	MCRF-ST 13kW 5 OHM J	13000 watt, 5 ohm resistor	15,900,000
	MCRF-ST 26kW 5 OHM J	26000 watt, 5 ohm resistor	32,400,000
	MCRF-ST 3.2kW 4.2 OHM J	3200 watt, 4.2 ohm resistor	5,400,000
	MCRF-ST 16kW 4 OHM J	16000 watt, 4 ohm resistor	21,400,000

Brake resistors (Case package type with thermostat sensor)		Temperature range: -50~200°C , Insulation resistance: over 20MΩ, Dielectric strength: AC 2,500V / 1 Min, Temperature coefficient: ±260 ppm / °C max, Thermostat sensor: B contact	
Tên hàng		Mô tả	Đơn giá (VNĐ)
	MCRF-ST 32kW 4 OHM J	32000 watt, 4 ohm resistor	38,500,000
	MCRF-ST 20kW 3.4 OHM J	20000 watt, 3.4 ohm resistor	23,200,000
	MCRF-ST 40kW 3.4 OHM J	40000 watt, 3.4 ohm resistor	45,200,000
	MCRF-ST 5kW 3 OHM J	5000 watt, 3 ohm resistor	7,300,000
	MCRF-ST 10kW 3 OHM J	10000 watt, 3 ohm resistor	12,500,000
	MCRF-ST 4.8kW 2.8 OHM J	4800 watt, 2.8 ohm resistor	7,300,000
	MCRF-ST 24kW 2.8 OHM J	24000 watt, 2.8 ohm resistor	30,500,000
	MCRF-ST 48kW 2.8 OHM J	48000 watt, 2.8 ohm resistor	58,300,000
	MCRF-ST 6kW 2.4 OHM J	6000 watt, 2.4 ohm resistor	8,250,000
	MCRF-ST 12kW 2.4 OHM J	12000 watt, 2.4 ohm resistor	15,300,000
	MCRF-ST 26kW 2.4 OHM J	26000 watt, 2.4 ohm resistor	32,400,000
	MCRF-ST 52kW 2.4 OHM J	52000 watt, 2.4 ohm resistor	75,000,000
	MCRF-ST 7.5kW 2 OHM J	7500 watt, 2 ohm resistor	9,800,000
	MCRF-ST 15kW 2 OHM J	15000 watt, 2 ohm resistor	16,500,000
	MCRF-ST 30kW 2 OHM J	30000 watt, 2 ohm resistor	35,100,000
	MCRF-ST 60kW 2 OHM J	60000 watt, 2 ohm resistor	79,400,000
	MCRF-ST 10kW 1.5 OHM J	10000 watt, 1.5 ohm resistor	12,500,000
	MCRF-ST 20kW 1.5 OHM J	20000 watt, 1.5 ohm resistor	23,200,000
	MCRF-ST 13kW 1.2 OHM J	13000 watt, 1.2 ohm resistor	15,900,000
	MCRF-ST 26kW 1.2 OHM J	26000 watt, 1.2 ohm resistor	32,400,000